M1500-SD-PR Professional SD/ uSD Duplicator



!!! The New IMI M1500-SD-PR Duplicator!!!

- USA Manufactured, Modular Construction, Easy to Change MicroSD Adapters
- Support for all SD Standards up to & Including UHS-1 SD & MicroSD Cards
- Patented Fast Duplication Allowing Fast Block Transfer & Card Register Addressing
- CIS & CID Register Access, Read/Write Functional Tests, Temporary Write Protect
- Stand Alone Operation: Master Image from Master Cards or Binary File
- Easy to Use Graphical Interface with User Supplied LCD/Key/Mouse
- Smart Copy for Copying User Data Only; Support for User Specified File Copy
- Binary Image Copy for Independence of the Operating System or File System
- Automatic Sizing & Checking of Master and Copy Cards
- Log Files with SQL Data Base, Network Connection via Ethernet

Home Office - USA 48389 Fremont Blvd., Ste 110 Web: www.imi-test.com **Fremont, CA 95035**

Email: sales@imi-test.com Tel: +1 408-942-1001



INTERNATIONAL MICROSYSTEMS



High Speed Duplication of SD & uSD Cards

The M1500 uses an IMI Patented SD interface which allows both super speed USB block data transfers as well as low level SD card register access.

Easily Changeable uSD adapters

The M1500 uses IMI custom designed MicroSD adapters that can be individually inserted into the 8 M1500 SD sockets and are held in place with a single removable bar.

Included Front Panel Functions for Each Section

Copy Master to Target Cards: Copy/Verify Master to Target Cards: Erase Target Cards: Verify Master to Target Cards: Set up User Job: Set up Card Type/Parameters: Copy Log to USB drive

Computer Interface with Optional Remote Data Logging

The M1500 has a 10/100/1000 Ethernet port which allows connection to standard networks.

Graphical Interface

With the attachment of a LCD/Key/Mouse, a full featured GUI running under Linux is available

Ordering Information

M1500-SD-PR : 8 Slot SD Duplicator M1500-uSD-8-B: 8 uSD Adapters with Retaining Bar (1 Reg'd for M1500-SD-8)

Specifications

Copy Capacity: 1Master, 7 Copy: with option to add suitable Micro SD Adapters Power Supply: 270W 100-240V SPS Display: 24 x 2 Backlit LCD Dimensions: 15"x15"x5 (38x38x13cm) Weight: 8lbs (4Kg) Interface: 10/100/1000 Ethernet, Front Panel USB 3.0; LCD/Key/Mouse Ports

Home Office - USA 48389 Fremont Blvd., Ste 110 Web: www.imi-test.com Fremont, CA 95035

Email: sales@imi-test.com Tel: +1 408-942-1001



INTERNATIONAL INCORPORATED